

# MAK METAMOL R

## Description

MAK Metamol R is specially made by blending mineral and fatty oils to give non-drip characteristics and also fortified with carefully selected additives.

## Application

This oil is specially designed to meet the lubrication requirements of percussion type pneumatic tools in general and rock drills in particular, where lubrication requirements are very critical.

## Benefits

- Exhibits extreme pressure properties
- possesses rust preventive properties

## Performance Level

- Proprietary grade

## Technical Specifications

Characteristics	ASTM	MAK Metamol R		
		100	181	220
Appearance	--	Bright & Clear	Bright & Clear	Bright & Clear
Density at 15°C	D1298	0.91	0.9393	0.9443
Viscosity Index	D2270	99	96	94
K.V at 40°C, cSt	D445	100.1	181.2	220.5
Flash Point, (COC), °C	D92	240	250	260
Pour point, °C	D97	-6	-6	-6

All the mentioned values are typical which may vary from batch to batch.

## Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided.

## Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet (MSDS) may be referred.

## Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

### **Bharat Petroleum Corporation Ltd.**

Product and Application Development Dept.  
 BPCL 'A' Installation, Sewree Fort Road, Sewree (East)  
 Mumbai -400015  
 E-mail: [MAKcustomercare2@bharatpetroleum.in](mailto:MAKcustomercare2@bharatpetroleum.in)  
 Tel No.: 022-24176351